

Nebula Networked AV™

Lighten every star



BYOM/Conference Room AV
Commercial / Digital Signage AV
Seamless Cross Display KVM
Residential AV



PB9700

USB C (DP Alt. Mode) / HDMI 4K HDR Input Support



Eco-Efficient AV



 **Dante®** AES67



Way to Control



AV Master Web Control



3rd Party Controller Integration



Keyboard HotKeys Control



- 4K60Hz 4:4:4 Video and Audio Over Inexpensive 1 Gbps Ethernet Network
- 36-bit color video engine support all HDR formats including Dolby Vision, HLG, HDR10+
- Ultra Low Latency Mode 4K60Hz video pass-thru below 4ms
- Dante/AES67 Audio Bridge In/Out interoperability with other audio equipment
- HDMI/USB-C auto detect/manual switch dual inputs on Sender. USB C support both DP Alt. Mode and USB 2.0 Link w/ just One cable


- USB-C/A ports on Receiver supports keyboard, mouse, USB drive, webcam & touchscreen
- Upscale/Downscale Video to fit display requirement
- HDMI eARC, ARC & S/PDIF Audio Return support
- Great Video Wall, Matrix and KVM Versatility
- Seamless Cross Multiple Displays KVM Switching
- Video Sub-Stream for viewing video snapshot on connected iPad/Tablet/Notebook
- Powerful Centralized Web Interface Management
- Easy Large Matrix/VideoWall Configuration with CSV File managed by MS Excel

Dante / AES67 Model	Sender/Tx: PB9700DNT-SE, Receiver/Rx: PB9700DNT-RE
AES67 Only Model	Sender/Tx: PB9700-SE, Receiver/Rx: PB9700-RE



PB9000W-SE

4K Over IP Wall Plate Sender



EU 2 Gang Form Factor

- PoE Powered (802.3af standard)
- HDMI Video Input up to 4K@60Hz 4:2:0 / 4K30Hz 4:4:4 HDR
- HDMI Audio up to 7.1ch LPCM/dts/Dolby ATMOS
- Dual Inputs: 1 x HDMI, 1 x VGA with 3.5mm Analog Audio
- IR Control: IR Emitter x 1, IR Receiver x 1
- Serial Control: RS232 (DB-9) x 1
- USB Pass-Thru: USB (Type B) x 1
- RJ45 Ethernet Port with Integrated PoE (802.3af)



PB9000-SE+H

4K Over IP Sender w/ HDMI Loop out, & S/PDIF TOSLINK Out

Inherits all PB9000 features with the following enhancements:



- **HDMI Loop out**
Supports local monitoring or AV Receiver connection, with pass-through for up to 4K video and Dolby Atmos/DTS:X audio.
- **Standalone S/PDIF TOSLINK Fiber Optics audio output**
Supports up to Dolby Digital (AC3). Ideal for connecting local video sources to nearby AV Receivers.


PB9000-RE

4K Over IP Receiver w/ Video Scaler




- Built-in Video Scaler for 1080p to 4K Up/Downscaling
- Independent Matrix Routing for Video, Audio, IR, RS232, USB
- Seamless Cross Display KVM Switching w/ USB 2.0 Pass-Thru
- CEC/IR/RS232 Control Signal Pass-Thru & IP Command
- Easy Video Wall Setup & Flexible Management via Web Interface
- Keyboard Hotkeys Control
- Video Snapshot


BYOM Ready by One USB-C. Connect, Present, and Collaborate Instantly.



Scalable & Flexible Digital Signage/Meeting Room/VideoWall



Residential AV Matrix





Aavara AV Master Web Control

Aavara
AVoIP
API


Dante
Managed
API

3 Party
Controller
Driver


STREAM
DECK

3rd party Controller integration

Controller driver provided, allowing controller to control Aavara Box directly by IP commands




Dante*/AES67 Audio Over IP




* Dante feature on selected PB9700 models only.

Independent Matrix Routing for Each Service

(Video, Audio, RS232, IR and USB)



CEC / IR / RS232 Over IP



Seamless Cross Display KVM

